EUROPEAN UNION



Delegation of the European Union to Bosnia and Herzegovina

Sarajevo,

Corrigendum No. 1

Project Title: Supply of ICT equipment for the parliaments in Bosnia and Herzegovina

Publication reference: EuropeAid/134-131/L/SUP/BA

Tender No: EC/BiH/TEN/13/002

Following changes in Annex II, Technical Specifications and Annex III, Technical offer have been made, as listed below:

1.3: Chases with Blade Servers

Requirements:

Server chassis form

- Blade server chassis max 8U with rackmounting accessories included supporting at least 8 servers
- o Chassis connectivity
- At least 8 10Gbps FCoE SFP+ ports for chassis uplink Gigabit Ethernet Ports
- Converged network (Ethernet and FC) must be supported through the same interfaces supporting virtual NIC and HBA for at least 128 VLAN's and/or VSAN's
- Support for FCoE 802.1Qbb, DCBX, IEEE 802.1Qaz
- Support for Layer 2 Trunk Failover to support active/standby

are corrected and read now:

- o Server chassis form
- Blade server chassis min. 8U to max. 16U with rackmounting accessories included supporting at least 8 servers
- Chassis connectivity
- At least 8 10Gbps FCoE SFP+ ports for chassis uplink Gigabit Ethernet Ports
- Converged network (Ethernet and FC) must be supported through the same interfaces supporting virtual NIC and HBA for at least 128 VLAN's and/or VSAN's
- Support for FCoE 802.1Qbb, DCBX, IEEE 802.1Qaz
- Support for active/standby

1.5: Server rack

Requirement:

o Size

- 19" server rack 600x2000x1000
- the front vented door with lock
- modular base and roof of the cabinet for cable entry

is corrected and reads now

o Size

- 19" server rack 600x2000x1000 +/-5%, must support offered Item 1.3 Server chassis form
- the front vented door with lock
- modular base and roof of the cabinet for cable entry

LOT 2: Desktops and Laptops

2.1: Desktop PC

Requirement:

Network interface

- Ethernet (RJ-45)
- Intel 82579LM Gigabit Network Connection (standard)

is corrected and reads now

Network interface

- Ethernet (RJ-45)
- Gigabit Network Connection (standard)

Requirement:

Monitor

• 19-inch +/- 5 %

is corrected and reads now

Monitor

• 20-inch +/- 10 %