


DESCRIPTION




Item 3- fire single-leaf door,
Class F-60.
Door Dimensions: 1000x2100mm

DOOR

Frame is made of galvanized sheet steel.
Door leaf: steel sheet 1 mm thick
reinforced with steel profiles.
Frame: metal sheet thickness of 2 mm.
Leaf thickness 62 mm, door leaf
is filled with special fireproof materials:
fireproof boards and
fire resistant strong wool.

SEALING

Sealing is done in three levels
and scope of the frame using
fire-resistant rubber and fire-resistant
expandable straps, the threshold
with firefighting tape.



INSTALLATION

-dry installation on new
gypsum cardboard wall .

FINISHING

Finishing - anticorrosive protection was
performed by electrostatic - plastification
according to RAL chart,
at the option of the designer.

ADDITIONAL EQUIPMENT

- Magnets
(for keeping the door in the open position)
- Fire steel lock
- Steel door handle coated with PVC
- Hydraulic door closing

* Item is to be ordered and prepared in
consultation with the designer and the investor.

* All measures are to be checked on the spot.

OPIS

Jednokrakla ostakljena pozicija

-konstrukcija pozicije izrađena
od al. profila, bez prekinutog
termičkog mosta, širine profila
70mm
-vrata kao i nadsvjetla
ostakljeni staklom 4+12+4mm

-predvidjeti sav potreban
visokokvalitetni okov.
-boja profila po izboru
projektanta.

Cijelu poziciju naručiti u
dogovoru sa projektantom i
investitorom,
a izraditi i ugraditi prema
uputama odabranog
proizvođača

**Sve mjere provjeriti na licu
mjesta.**

SCALE/RAZMJERA 1:50

LEVEL/SPRAT	LEFT/LIJEVA	RIGHT/DESNA	PCS./KOM
BASEMENT FLOOR/ PODRUM	0	0	0
GROUND FLOOR/ PRIZEMLJE	0	1	1
1st FLOOR/ PRVI SPRAT	0	0	0
2nd FLOOR/ DRUGI SPRAT	0	0	0
3rd FLOOR/ TREĆI SPRAT	0	0	0
4th FLOOR/ ČETVRTI SPRAT	0	0	0

TOTAL PCS./UKUPNO	0	1	1
-------------------	---	---	---

