

ANNEX II + IIA

TECHNICAL SPECIFICATIONS

Contract title: Improve technical working conditions of court police; Equipment for Court Police

(including changes in Corrigendum 1 & 2); CHANGES ARE MADE IN Lots 1,2,4 and 5

Publication reference: 136617/DH/SUP/BA

Technical reference: EC/BiH/TEN/15/001

Lot 1 – Judicial Police Vehicles

Lot 2 – Police Riot Control Equipment

Lot 3 – Security Equipment

Lot 4 – Video surveillance system in judicial institutions of Tuzla

Lot 5 – IT equipment

Lot 6 – Radio Communication Equipment

Lot 7 – Access Control Equipment

Column 1-3 should be completed by the Contracting Authority

Column 5-4 should be completed by the tenderer

Column 6 is reserved for the evaluation committee

Annex III - the Contractor's technical offer

The tenderers are requested to complete the template on the next pages:

- Columns 1-3 completed by the Contracting Authority show the required specifications (not to be modified by the tenderer),
- Column 4 is to be filled in by the tenderer and must detail what is offered (for example the words “compliant” or “yes” are not sufficient)
- Column 5 allows the tenderer to make comments on its proposed supply and to make eventual references to the documentation

The documentation supplied should clearly indicate (highlight, mark) the models offered and the options included, if any, so that the evaluators can see the exact configuration. Offers that do not permit to identify precisely the models and the specifications may be rejected by the evaluation committee.

The offer must be clear enough to allow the evaluators to make an easy comparison between the requested specifications and the offered specifications.

Lot 1 – Judicial Police Vehicles

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
1.1	<p>(Unmarked police) motor vehicle to transport minors and protected witnesses with additional equipment and aftermarket upgrades</p> <p>Basic vehicle characteristics:</p> <ul style="list-style-type: none"> ➤ Displacement (cm / 3): a minimum of 1890; ➤ Power output: 77 kW minimum; ➤ Number of gears: minimum 5 + R (Manual transmission); ➤ Number of doors: 4 or 5; ➤ Colour: metallic black or metallic grey; ➤ Drive: Front-wheel; ➤ Fuel: Diesel; ➤ Seats: 1 + 4; ➤ Length / Height (mm): minimum 4650/1450; ➤ Wheelbase (mm): a minimum of 1510; ➤ Cargo area (volume of the trunk): a minimum of 430 l <p>Minimum vehicle equipment:</p> <ul style="list-style-type: none"> ➤ ABS braking system; ➤ traction control system; ➤ adjustable power steering wheel height and depth, ➤ airbags for driver and front passenger, plus side airbags in the front; ➤ adjustable driver's seat; ➤ electrical windows at least on the front doors of the driver and front passenger; ➤ board computer; ➤ automatic air conditioning ; ➤ radio with 4 speakers (factory installed); ➤ ability to play music from (factory installed): CD/MP3 CD and/or USB – stick, SD – card or equivalent ➤ appropriate steel rims with tires (M + S); ➤ adequate spare tire with steel rim; 	10			

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ heated power side-view mirrors; ➤ halogen fog lights; ➤ additional brake light in the rear part; ➤ armrest in front seat; ➤ remote central locking and adequate security system - alarm; ➤ upholstery - appropriate for the driver's seat, front passenger's seat and backseat (made of fabric or eco-leather); ➤ built-in mechanical transmission lock (anti-theft); ➤ set of required equipment in the vehicle (spare bulbs, first aid kit, tow rope, warning triangle); ➤ rubber floor mats underneath driver's seat, front passenger's seat and backseat; <p>Upgrades with the following equipment:</p> <ul style="list-style-type: none"> ➤ Security reflective film <ul style="list-style-type: none"> ○ Minimum film thickness 200 microns ○ Percentage of visible light transmission 65% (+/- 5%) ○ Reflection of UV rays minimum 90% ○ Total reflection of sun energy 80% (+/- 5%) ➤ Installation of VHF radio station including: <ul style="list-style-type: none"> ○ Frequency range 136-174MHz ○ Power up to 25W ○ Power supply 12V ○ Number of channels 4 minimum ○ Vehicle mounting ○ Signalling cell V ○ Built in scrambler ○ Built in internal speaker ○ External speaker port ○ Channel interval 25/20/12,5 ○ MIL-STD-810-C/D/E ➤ Installation of lighting and acoustic signals including: <ul style="list-style-type: none"> ○ Led diode of 3rd generation ○ Lifespan of 50.000 hours ○ Magnetic mount ○ Siren with different tones ○ Siren power 100 W 				

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ○ Filter colour (blue) ○ IP 55 ○ Electronic amplifier –vehicle mounted ○ LED „strobe“ lights mounted in the front grid mask and rear signal lights (stop lights) of the vehicle, filter colour red-blue 				
1.2	<p>(Marked police) motor vehicle - a van to transport detained persons with additional equipment and aftermarket upgrades</p> <p>Basic vehicle characteristics:</p> <ul style="list-style-type: none"> ➤ Displacement (cm / 3): a minimum of 1890; ➤ Power output: 90 kW minimum; ➤ Number of gears: minimum 5 + R (Manual transmission); ➤ Number of doors: 4 or 5; ➤ Colour: white; ➤ Drive: Front-wheel; ➤ Fuel: Diesel; ➤ Seats: driver's, front passenger's and three back seats ➤ An overall length ranging from 4700 to 5000 mm / Height (mm): minimum 4880/1850; Wheelbase (mm): minimum 2900; <p>Minimum vehicle equipment:</p> <ul style="list-style-type: none"> ➤ ABS braking system; ➤ traction control system; ➤ adjustable power steering wheel height and depth, ➤ airbags for driver and front passenger; ➤ adjustable driver's seat; ➤ electrical windows at least on the front doors of the driver and front passenger; ➤ right side sliding door; ➤ opening window on the sliding door; ➤ double rear doors with no windows - sheet metal; ➤ side windows of cargo area closed with sheet metal; ➤ partition fixed behind the second row seating and compartment for the transport of persons; ➤ air conditioner that will cover the entire interior/ passenger 	2			

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<p>compartment and compartment for the transport of persons;</p> <ul style="list-style-type: none"> ➤ installations for radio with 4 speakers, ➤ spare tire with steel rim, tools and car jack; ➤ heated power side-view mirrors; ➤ halogen fog lights; ➤ remote central locking and alarm; ➤ appropriate steel rims with tires (M + S); ➤ set of required equipment in the vehicle (spare bulbs, first aid kit, tow rope, warning triangle); ➤ rubber floor mats underneath driver's seat, front passenger's seat and backseat; <p>Upgrades with the following equipment:</p> <ul style="list-style-type: none"> ➤ Two (hidden or protected) mini surveillance cameras mounted on opposite sides, with an IR reflector within the housing to capture the compartment for the transport of persons (cage) and a LCD 7" (18 cm diagonally) monitor placed in front of the front passenger; ➤ Spotlight on the roof above the rear door; ➤ Intercom for listening to and communicating with a person in cage, whose control system is installed next to the front passenger; ➤ Fan for the cage mounted on the roof inside with a switch; ➤ Security reflective film (for glass of driver's cab and the middle row of seats) <ul style="list-style-type: none"> ○ Minimum film thickness 200 microns ○ Percentage of visible light transmission 65% (+/- 5%) ○ Reflection of UV rays minimum 90% ○ Total reflection of sun energy 80% (+/- 5%) ➤ Lighting (blue) and acoustic signalling devices mounted on the roof (the new LED technology) with siren amplifier and a microphone in the cabin; ➤ Strobe warning lights built into the brake lights - 2 pieces; ➤ Installation of VHF radio station including: <ul style="list-style-type: none"> ○ Frequency range 136-174MHz ○ Power up to 25W 				

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ○ Power supply 12V ○ Number of channels 4 minimum ○ Vehicle mounting ○ Signalling cell V ○ Built in scrambler ○ Built in internal speaker ○ External speaker port ○ Channel interval 25/20/12,5 ○ MIL-STD-810-C/D/E 				
1.3	<p>(Marked police) motor vehicle to transport detained persons with additional equipment and aftermarket upgrades</p> <p>Basic vehicle characteristics:</p> <ul style="list-style-type: none"> ➤ Displacement (cm / 3): a minimum of 1500; ➤ Power output: 65 kW minimum; ➤ Number of gears: minimum 5 + R (Manual transmission); ➤ Number of doors: 4 or 5; ➤ Colour: white; ➤ Drive: Front-wheel; ➤ Fuel: Diesel; ➤ Seats: 1+4; ➤ Length / Height (mm): minimum 4350 /1800; ➤ Wheelbase (mm): minimum 2650; ➤ Cargo area (volume of the trunk): minimum width of 1200 mm (+/- 5%); minimum length of 800 mm (+/- 5%); minimum height of 1000 mm (+/- 5%). ➤ NOTE: The minimum length of the cargo area/trunk means the length between the partition fixed behind the second row seating and the double back door. <p>Minimum vehicle equipment:</p> <ul style="list-style-type: none"> ➤ ABS braking system; ➤ traction control system; ➤ adjustable power steering wheel height and depth, ➤ airbags for driver and front passenger; ➤ adjustable driver's seat; 	8			

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ electrical windows at least on the front doors of the driver and front passenger ➤ double rear door, ➤ semi-automatic air conditioning; ➤ interior mirror on the windscreen; ➤ opening window on the sliding door: ➤ double rear doors with no windows - sheet metal; ➤ side windows of cargo area closed with sheet metal; ➤ partition fixed behind the second row seating and compartment for the transport of persons; ➤ air conditioner that will cover the entire interior/ passenger compartment and compartment for the transport of persons; ➤ RCD with four speakers, ➤ spare tire with steel rim, tools and car jack; ➤ heated power side-view mirrors; ➤ halogen fog lights; ➤ remote central locking and alarm; ➤ appropriate steel rims with tires (M + S); ➤ set of required equipment in the vehicle (spare bulbs, first aid kit, tow rope, warning triangle); ➤ Rubber floor mats underneath driver's seat, front passenger's seat and second row seating. <p>Upgrades with the following equipment:</p> <ul style="list-style-type: none"> ➤ Light (blue) and audio signalling devices fixed to the roof (the new LED technology) with siren amplifier and a microphone in the cabin; ➤ Security reflective film (glass on the side sliding door) <ul style="list-style-type: none"> ○ Minimum film thickness 200 microns ○ Percentage of visible light transmission 65% (+/- 5%) ○ Reflection of UV rays minimum 90% ○ Total reflection of sun energy 80% (+/- 5%) ➤ Installation of VHF radio station including: <ul style="list-style-type: none"> ○ Frequency range 136-174MHz ○ Power up to 25W 				

1	2	3	4	5	6
Item Number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ○ Power supply 12V ○ Number of channels 4 minimum ○ Vehicle mounting ○ Signalling cell V ○ Built in scrambler ○ Built in internal speaker ○ External speaker port ○ Channel interval 25/20/12,5 ○ MIL-STD-810-C/D/E ➤ Police marks (insignias) on the vehicle in accordance with the Rules on Police Insignias of the Court Police of Republika Srpska available on the web site of the Court Police of Republika Srpska 				

The contractor has to deliver vehicles fully upgraded according to the specification to the delivery locations mentioned below.

Warranty period for all items: 1 year. Commercial warranty as granted by the manufacturer.

Delivery locations:

Institution	City	Address	1.1	1.2	1.3	Remark
Court Police Administration of FBiH	Sarajevo	Valtera Perića 15 71000 Sarajevo	5			Considering all equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH, upon delivery and provisional acceptance to/at the Head Office, distribution will be done by the Head Office to the following locations: Head Office of the Court Police of FBiH Sarajevo Intervention-Operational Unit Sarajevo Section Mostar Section Tuzla Section Zenica
Court Police Administration of RS	Banja Luka	Aleja Svetog Save bb 78000 Banja Luka	5	2	6	Considering all equipment is to be recorded as an asset of the Head Office of the Court Police of RS, upon delivery to and provisional acceptance at the Head Office, distribution will be done by the Head Office to the following locations: District Court Police Center Banja Luka (1.1; 1.3) District Court Police Center Bijeljina (1.1; 1.3) District Court Police Center Istočno Sarajevo (1.1; 1.3) District Court Police Center Doboj(1.1; 1.3) District Court Police Center Trebinje (1.1; 1.3) Intervention Unit of the Court Police Banja Luka (1.2x2; 1.3)
Judicial Commission of the Brčko District of BiH	Brčko	Trg pravde 10 76100 Brčko			2	Court Police of Brčko District
TOTAL			10	2	8	

Lot 2 – Police Riot Control Equipment

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
2.1	<p>Anti-riot suit</p> <p>Very hard outer layer made of special plastic-coated fabric made of materials harmless to human body;</p> <p>This product consists of the following parts:</p> <ul style="list-style-type: none"> ➤ Trunk protector must be composed of two protective layers: <ul style="list-style-type: none"> • Front and rear plates are made of hard polycarbonate plastic that provides extensive protection and resistance to the external violence. Front plate anatomically curved to provide maximum protection to chest and abdomen. Both front and back armour plates have developed strengthening features against outer strike; • Shock-absorbing padded layer made of foam / sponge material. This layer should allow easy mobility and close-fitting; ➤ Biceps protector must be composed of a hard polycarbonate shell with adjustable rubber in the centre; ➤ Elbow and forearm protector must be composed of the same material as the biceps protectors. Both protectors are equipped with elastic straps and Velcro to attach to the hand; ➤ Thigh protector is made of hard polycarbonate plastic. The foam-coated fabric and stitched internally with the thigh pads. Adjustable elastic straps for attaching the pelvis and flank protector; ➤ Flank protector made of hard plastic base and foam; ➤ Knee and shin protector made of hard polycarbonate plastic, foam stitched internally, with elastic straps and Velcro 	50			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	for detachable and adjustable ankle and dorsal foot protector; <ul style="list-style-type: none"> ➤ The total weight of the suit shall be a maximum of 5.0 kg; ➤ It can stand minimum 15J puncture kinetic energy; ➤ It can stand minimum 1000J impact kinetic energy; ➤ Impact absorbing ability must be a minimum of 80J. ➤ The suits have to be made in different sizes (for details see Annex "Specification of sizes"). ➤ Sizes: for details see Annex "Specification of sizes for Lot 2"). 				
2.2	Riot protection helmet with visor Helmet must consist of three (3) elements: <ol style="list-style-type: none"> 1. Hard shell made of highly resistant thermoplastic material with Kevlar reinforcement, resistant to impact and penetration of projectiles, light weight for easy wearing, 2. Padding designed for user's comfort and designed to allow shock absorption, 3. Hinge-up visor, designed to protect the user's face, of minimum thickness of 3 mm; <ul style="list-style-type: none"> ➤ The helmet must provide maximum protection against tossed, falling or otherwise launched missiles, stones, metal objects, bats and any other objects a police officer may encounter. The structure must be resistant to all forms of penetration and successfully withstand all mechanical negative impacts; ➤ All outward parts must be chemically protected, corrosion-resistant and non-flammable; ➤ All parts must be made to allow disassembling, cleaning and other operations without any special tools; ➤ The helmet must allow the use of gas masks and communication devices; ➤ The helmet must meet the level of protection -V50 + 450 m / s and must comply with E / ECE-324: 1998 and EN 397 in 1995. When submitting bids, the bidder shall submit a certificate of quality; 	50			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ The hard shell must be made from a single piece, cast from a special thermoplastic material with Kevlar reinforcement or equivalent; ➤ The hard shell must be designed to provide great freedom of movement without restricting the flexibility of head movement or reduction of the visual field; ➤ Helmet must not have openings; ➤ The helmet should weigh less than 2800 g (size XL or medium size); ➤ The visor has to be attached to the aluminium shell, which includes a hard rubber gasket that forms a seal between the visor and the upper edge of the hard shell; ➤ The visor must be attached to the hard shell at two pivot points; ➤ The helmet must be black; ➤ The region of the nape of the head must have extra protection and be padded with foam wrapped in lining made of material that absorbs moisture and perspiration, with a possibility of separating the protection from the helmet as needed; ➤ The lining of the inner layer with the maximum ability to protect against moisture and remove it from the user's head outside; ➤ The helmet chinstrap assembly (with chin cap) must be attached to the inside of the hard shell; ➤ The strap must have foam pads (on the left and right side) lined with leather to protect the user's face while wearing / fixing the helmet and are anti-irritation; ➤ The two halves of the chinstrap assembly must be connected and adjustable with a quick release buckle; ➤ The visor must be made of durable material, minimum thickness of 3 mm; ➤ The visor must be scratch resistant; ➤ The visor must not have any sharp edges, corners or protrusions; ➤ The neck cover must be made of one-piece "PROBAN" fabric 				

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<p>or equivalent, which is fixed to the inside of the helmet with the help of thumb knobs snaps and, if necessary, can be removed;</p> <p>➤ Sizes: for details see Annex "Specification of sizes for Lot 2").</p>				
2.3	<p>Anti-riot police shield</p> <p>➤ Must be made of transparent high quality polycarbonate which provides a high level of protection and absorption of various types of attacks and resistance to penetration, throwing stones, iron balls and so on;</p> <p>➤ The shield must not have sharp edges;</p> <p>➤ Shield handle must be made of polymer with steel reinforcements;</p> <p>➤ Shield thickness at least 3.5 mm;</p> <p>➤ Shield height between 900 and 1220 mm;</p> <p>➤ Shield breadth between 500 and 620 mm;</p> <p>➤ Must provide protection from fragments at a V50 - 230 m / s;</p> <p>➤ Tests to have been passed are:</p> <ul style="list-style-type: none"> ○ Ballistic test V50, ○ Mechanical test according to European standards DIN EN 166: 2002, DIN EN 12825: 2002, DIN EN 13213: 2001, ○ Test of the protection against acid as well as organic materials (no visible change on the surface of the shield of the following substances: 40% NaOH, 32% HCl, 65% HNO₃ and petrol / diesel), ○ Test of the protection against large mass impacts (energy of 392 J at a speed of 4.4 m / s), ○ Test of the protection against mechanical impacts (energy of 26.5 J at a speed of 4.4 m / s); <p>➤ The shield must have markings SUDSKA-SUDBENA-SUDSKA in the first row and POLICIJA – POLICIJA in the second row in spaced letters in Bosnian, Croatian and Serbian language and Latin and Cyrillic alphabet in white colour.</p>	70			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
2.4	Anti-riot police gloves <ul style="list-style-type: none"> ➤ The exterior of the glove must be made of leather in black colour; ➤ The inside of the glove must be of Kevlar or equivalent material with the same characteristics; ➤ The rear of the glove must have carbon leather inserted, while the knuckles are protected with EVA foam, which protects against injuries; <p>Sizes: for details see Annex "Specification of sizes for Lot 2").</p>	50			
2.5	Anti-riot (tonfa) baton <ul style="list-style-type: none"> ➤ Telescopic tonfa baton must be made of high quality duralumin ➤ It must be resistant to oxidation ➤ Length of telescopic tonfa baton when closed must be less than 30 cm; ➤ Length of telescopic tonfa baton when opened must be more than 55 cm; ➤ Weight of telescopic tonfa baton must be less than 900 grams; ➤ Rotating 360° expandable baton holder for application to duty belt. 	50			
2.6	Bullet-proof vest <ul style="list-style-type: none"> ➤ Bullet-proof vest must comply with the protection level IIIA under 0101.04 National Institute of Justice standard; ➤ The protective panel must be made of Twaron, Thor or equivalent; ➤ Panel pockets should have dimensions 250mm width / 300mm height. ➤ The vest must be made of durable material with a mixture of polyester and cotton; ➤ Fully adjustable shoulder; ➤ The vest must have adjustable elastic straps that provide a 	100			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<p>perfect opportunity to fit the vest to the body;</p> <ul style="list-style-type: none"> ➤ Weight vests must be a maximum of 4.0 kg; ➤ Sizes: for details see Annex "Specification of sizes for Lot 2"). ➤ Colour: Black ➤ The vest has markings SUDSKA-SUDBENA-SUDSKA in the first row and POLICIJA – POLICIJA in the second row in spaced letters in Bosnian, Croatian and Serbian language and Latin and Cyrillic alphabet of appropriate size on the left side of the front of the vest at chest height and on the back of the vest (the width of the back) in white color. 				
2.7	<p>Bullet-proof helmet</p> <ul style="list-style-type: none"> ➤ Ballistic protection: IIIA, V50 = 650m / s ➤ Ballistic material: Aramid ➤ Colour: Black ➤ Weight: S-small: maximum 1510g, M-medium: maximum 1560g, L-large: maximum 1660g ➤ In compliance of NIJ 0106.01 standard, STANAG 2920 or equivalent ➤ The helmet must have the inner lining with integrated "SHOTECK" shock absorption system, in accordance with standard EN397 ➤ The helmet must be made with the new "BOTELLES" and "EBSP" frame ➤ Space between the outer layer and the lining should be between 12 and 14 mm ➤ The helmet must have a ventilation system ➤ The inner lining must be made of a particular sponge covered in leather and of adjustable height ➤ The helmet must have an adjustable strap for fastening with chin cap ➤ The strap must be fastened using a quick "PRESS" buckle. ➤ The strap must have a security clasp that is automatically activated by force of 150-250 N. 	50			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	➤ Sizes: for details see Annex "Specification of sizes for Lot 2".				

The contractor must deliver above specified items at the delivery locations mentioned below.

Warranty period for all items: 1 year. Commercial warranty as granted by the manufacturer.

Specification of sizes for Lot 2										
2.1 Anti-riot suit		2.2 Bullet-proof helmet with visor		2.4 Anti-riot police gloves			2.6 Bullet-proof vest		2.7 Bullet-proof helmet	
size	quantity	size	quantity	size	size of fist without a thumb in cm	quantity	Size	quantity	size	quantity
US (EU)		US (EU)		US (EU)			US (EU)		US (EU)	
-	-	-	-	-	-	-	S (46-48)	2	-	-
M (48-50)	4	M (56-57)	10+6	M (9)	24	10	M (48-50)	4+4	M (56-57)	10+6
L (50-52)	20	L (58-59)	15+20	L (10)	26	20	L (50-52)	20+13	L (58-59)	15+20
XL (54-56)	20	XL (60-61)	15+20	XL (11)	27,5	15	XL (54-56)	20+14	XL (60-61)	15+20
XXL (56-58)	6	XXL (62-63)	10+4	XXL (12)	28,5	5	XXL (56-58)	6+17	XXL (62-63)	10+4

Delivery locations:

Institution	City	Address	2.1	2.2	2.3	2.4	2.5	2.6	2.7	Remark
Court Police Administration of FBiH	Sarajevo	Valtera Perića 15, 71000 Sarajevo	50	50	50	50	50	50		Considering all equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH, upon delivery to and provisional acceptance at the Head Office, distribution will be done by the Head Office to the following locations: Tuzla - 15 sets Zenica - 10 sets Bihać - 10 sets Mostar - 10 sets Travnik - 5 sets
Ministry of Justice of BiH, Court Police of BiH	Sarajevo	Kraljice Jelene 88, 71000 Sarajevo			20			50	50	Court Police of BiH is an organizational unit of the Ministry of Justice of BiH. Equipment will be delivered to and provisional acceptance done at the Court Police of BiH location but it will be an asset of the Ministry of Justice of BiH.
TOTAL			50	50	70	50	50	100	50	

Lot 3 – Security Equipment

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
3.1	Reflective and window safety film <ul style="list-style-type: none"> ➤ Safety and reflective film for solar control and privacy; ➤ Strengthens glass – improves safety and prevents the shards from flying around after violent impact, bomb explosion and deliberate attacks; ➤ Adhesive acrylic-based heat-resistant film, quickly adheres to glass; ➤ Film thickness: minimum of 200 microns; ➤ Percentage of visible light transmission (VLT) of: 20% (+/- 10%); ➤ Reflection of UV radiation: a minimum of 90%; ➤ Total reflection of solar energy: 80% (+/- 10%). ➤ European Standard applied to the product: EN12600 – Safety – Resistance against impact 	887,80m2			

For item 3.1: Contractor must be authorized for distribution and installation of external and internal films, posses and submit relevant valid certificates for the year 2015 or 2016 issued by manufacturer. The safety film installation shall be done in accordance with manufacturer's instructions. At least one worker certified by the manufacturer for the installation of safety film has to be permanently present during the film installation. Contractor must deliver and install the items at the delivery locations specified below.

Warranty period: 1 year warranty. Commercial warranty as granted by the manufacturer.

Delivery locations:

Institution	City	Address	3.2	Remark
Judicial Commission of the Brčko District of BiH	Brčko	Trg pravde 10, 76100 Brčko	63,20m2	
Supreme Court of FBiH	Sarajevo	Valtera Perića 15, 71000 Sarajevo	170,17m2	
Cantonal Court	Sarajevo	Šenoina 1, 71000 Sarajevo	199,07m2	
Cantonal Prosecutor's Office	Sarajevo	Radićeva 6, 71000 Sarajevo	59,14m2	
Cantonal Court	Mostar	Ante Starčevića 20, 88000 Mostar	62,28m2	
Cantonal Court	Zenica	Masarykova 50, 72000 Zenica	60,98m2	
Municipal Court	Zenica	Trg BiH 2, 72000 Zenica	103,17m2	
Cantonal Court	Novi Travnik	Kralja Tvrtka bb, 72290 Novi Travnik	85,34m2	
Municipal Court	Ljubuški	Zrinsko Frankopanska bb, 88320 Ljubuški	70,90m2	
TOTAL			887,80m2	

DIMENSIONS OF THE OPENINGS

Location	Apellation and Basic Court of Brčko District	
Specific location		
Number of openings	Dimensions	Total
22	1,22m x 1,87m	50,16m2
8	0,87m x 1,87m	13,04m2
Total		63,20m2

Location	Supreme Court of the Federation BiH	
Specific location	Ground floor	
Number of openings	Dimensions	Total
8	1,70m x 4,43m	60,24m ²
6	1,70m x 4,45m	45,39m ²
1	1,68m x 4,47m	7,50m ²
2	1,70m x 2,90m	9,86m ²
2	1,40m x 1,70m	4,76m ²
1	8,30m x 2,00m	16,60m ²
1	2,90m x 0,50m	1,45m ²
1	0,60m x 2,77m	1,66m ²
1	2,70m x 1,30m	3,51m ²
1	4,85m x 3,96m	19,20m ²
Total		170,17m²
Location	Cantonal Court in Sarajevo	
Specific location	Court Room no. 2	
Number of openings	Dimensions	Total
5	2,50m x 1,40m	17,50m ²
1	2,50m x 1,10m	2,75m ²
Total		20,25m²
Specific location	Windows of a basement area in street Šenoina and street Branilaca Sarajeva	
Number of openings	Dimensions	Total
15	1,30m x 1,10m	21,45m ²
4	1,20m x 1,10m	5,28m ²
4	1,10m x 0,80m	3,52m ²
Total		30,25m²

Specific location	Entrance (official entrance)	
Number of openings	Dimensions	Total
1	2,30m x 2,20m	5,06m2
1	2,30m x 1,40m	3,22m2
Total		8,28m2
Specific location	Windows – ground floor (street Šenoina and Branilaca Srajeva)	
Number of openings	Dimensions	Total
26	2,50m x 1,40m	91m2
4	2,60m x 2,00m	20,80m2
Total		111,80m2
Specific location	Ground floor (Court Police premises)	
Number of openings	Dimensions	Total
2	2,60m x 1,15m	5,98m2
Specific location	Ground floor (Association of Mediators)	
Number of openings	Dimensions	Total
1	2,50m x 1,10m	2,75m2
Specific location	Ground floor (Restaurant for lawyers)	
Number of openings	Dimensions	Total
2	1,10m x 0,80m	1,76m2
Specific location	Municipal court Sarajevo (Land Registry in street Branilaca Sarajeva)	
Number of openings	Dimensions	Total
3	2,50m x 2,40m	18m2
Total		28,49m2
Location	Cantonal Prosecutor's Office in Sarajevo	
Specific location	Basement area	
Number of openings	Dimensions	Total
2	1,60m x 0,70m	2,24m2

2	1,30m x 0,70m	0,91m2
2	1,30m x 1,20m	3,12m2
1	0,90m x 0,50m	0,45m2
Total		6,72m2
Specific location	Ground floor	
Number of openings	Dimensions	Total
14	2,00m x 1,20m	33,60m2
5	2,00m x 1,70m	17,00m2
1	1,40m x 1,30m	1,82m2
Total		52,42m2
Location	Cantonal Court in Mostar	
Specific location	Ground floor	
Number of openings	Dimensions	Total
13	1,00m x 2,00m	26m2
Specific location	First floor (court president's office)	
Number of openings	Dimensions	Total
2	1,20m x 2,30m	5,50m2
Specific location	First floor (large court room)	
Number of openings	Dimensions	Total
5	1,50m x 3,00m	22,50m2
Specific location	First floor (little court room)	
Number of openings	Dimensions	Total
3	1,20m x 2,30m	8,28m2
Total		62,28m2
Location	Cantonal Court in Zenica	
Specific location	Glass openings – ground floor	
Number of openings	Dimensions	Total
2	0,40 x 1,65m	1,32m2
2	0,40 x 1,60m	0,48m2

2	0,80 x 1,55m	2,48m2
4	0,60 x 0,80m	1,92m2
2	0,20 x 0,60m	0,24m2
2	0,20 x 1,65m	0,66m2
2	0,80 x 1,65m	2,64m2
Total		9,74m2
Specific location	Windows	
Number of openings	Dimensions	Total
14	1,20m x 1,25m	21m2
14	0,27m x 0,97m	3,66m2
14	0,91m x 1,17m	14,90m2
12	0,55m x 0,85m	5,61m2
7	0,20m x 0,27m	0,42m2
6	1,18m x 0,45m	3,19m2
1	1,20m x 1,20m	1,44m2
1	0,91m x 1,12m	1,02m2
Total		51,24m2
Location	Cantonal Court in Novi Travnik	
Specific location	Ground floor – East part	
Number of openings	Dimensions	Total
3	1,30m x 0,90m	3,51m2
15	1,30m x 0,80m	15,60m2
Total		19,11m2
Specific location	Ground floor – West part	
Number of openings	Dimensions	Total
21	1,10m x 0,60m	13,86m2
21	0,50m x 0,60m	6,30m2
8	1,50m x 0,85m	10,20m2
3	1,35m x 0,82m	3,32m2

3	1,32m x 0,62m	2,45m2
3	0,64m x 0,62m	1,19m2
1	1,32m x 0,70m	0,92m2
1	0,56m x 0,70m	0,39m2
Total		38,63m2
Specific location	Ground floor – North part	
Number of openings	Dimensions	Total
1	1,45m x 1,35m	1,95m2
2	1,45m x 0,50m	0,72m2
1	1,45m x 0,70m	1m2
1	1,45m x 1,20m	1,74m2
Total		5,41m2
Specific location	Court room no. 24	
Number of openings	Dimensions	Total
4	1,45m x 1,40m	8,12m2
4	0,66m x 1,40m	3,69m2
Total		11,81m2
Specific location	Court room no. 16	
Number of openings	Dimensions	Total
1	1,35m x 0,47m	0,63m2
1	1,35m x 0,62m	0,83m2
1	0,65m x 0,46m	0,29m2
1	0,65m x 0,62m	0,40m2
1	1,35m x 0,50m	0,67m2
1	0,57m x 0,48m	0,27m2
6	1,32m x 0,62m	4,91m2
6	0,64m x 0,62m	2,38m2
Total		10,38m2
Location	Municipal Court in Ljubuški	

Specific location	Ground floor	
Number of openings	Dimensions	Total
6	2,87m x 1,80m	30,99m2
4	2,87m x 1,90m	21,81m2
2	1,33m x 1,80m	4,78m2
1	2,45m x 1,80m	4,41m2
1	3,30m x 2,70m	8,91m2
Total		70,90m2
Location	Municipal / Cantonal Court / Prosecutor's Office in Livno	
Specific location	Ground floor	
Number of openings	Dimensions	Total
4	1,34m x 1,70m	9,12m2
6	2,05m x 1,6 m	20,30m2
Total		29,42m2
Location	Cantonal Prosecutor's Office in Tuzla	
Specific location	Ground floor	
Number of openings	Dimensions	Total
1	4,90m x 3,23m	15,82m2
2	0,79m x 1,20m	1,89m2
1	2,00m x 0,80m	1,60m2
12	0,85m x 1,56m	15,91m2
1	2,20m x 2,50m	5,50m2
1	2,20m x 1,85m	4,07m2
3	0,70m x 1,06m	2,22m2
Specific location	First floor	
Number of openings	Dimensions	Total
8	0,57m x 1,38m	6,29m2
1	1,97m x 2,90m	5,71m2

1	1,20m x 4,00m	4,80m2
18	0,90m x 1,45m	23,49m2
Total		87,30m2
TOTAL ALL		887,80m2

Lot 4 – Video surveillance system in judicial institutions of Tuzla

Video surveillance system will cover building of the following judicial institutions in Tuzla (Cantonal court, Municipal Court and Cantonal Prosecutors' Office). This system must be IP technology based. Monitoring of the video surveillance system will be performed by the Court Police of Federation of Bosnia and Herzegovina, Department Tuzla from their operations room.

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
4.1	32- channel IP network video recorder <ul style="list-style-type: none"> ➤ IP video input 32 channel ➤ HDMI and VGA output ➤ HDD SATA up to 4TB capacity ➤ Up to 5 MP (2560x190) recording resolution ➤ Alarm in, alarm out 	1			
4.2	64-channel IP network video recorder <ul style="list-style-type: none"> ➤ IP video input 64 channel ➤ HDMI and VGA output ➤ HDD SATA up to 4TB capacity ➤ Up to 5 MP (2560x190) recording resolution ➤ Alarm in, alarm out 	1			
4.3	Internal Dome camera <ul style="list-style-type: none"> ➤ 1.3 MP ➤ Lens 2,8-12mm ➤ Day & night ICR up to 20m ➤ Resolution 1280-960 ➤ IP 66 ➤ HD real time video ➤ Vandal-proof ➤ Mount kit included 	45			
4.4.	Rotating camera network controller (keyboard) <ul style="list-style-type: none"> ➤ PTZ control with three axis joystick ➤ LCD display 	1			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ Support for 15 users ➤ - 				
4.5	External rotating camera <ul style="list-style-type: none"> ➤ 1.3 MP ➤ 20X optical zoom, 16x digital zoom ➤ Day & night, 3D DNR, Digital WDR ➤ Resolution 1280-960 ➤ IP 66 ➤ HD real time video ➤ 3D intelligent positioning ➤ Mount kit included 	5			
4.6	External IR cameras, day/night <ul style="list-style-type: none"> ➤ 1.3 MP ➤ Lens 2,8-12mm ➤ Day & night ICR up to 30m ➤ Resolution 1280-960 ➤ IP 66 ➤ HD real time video ➤ Mount kit included 	17			
4.7	24-port POE switch <ul style="list-style-type: none"> ➤ 24 port ➤ POE ➤ PoE Power up to 15.4 Watts for every 802.3af PoE port ➤ 19" Rack mount kit included 	4			
4.8	Wireless panic button <ul style="list-style-type: none"> ➤ 12 VDC ➤ 150m range ➤ LED indicator of transmission 	6			
4.9	RACK 7 HE <ul style="list-style-type: none"> ➤ Dimensions: 400x400x400 	4			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ System door and side locks and two keys ➤ Thermally processed door glass, minimum 4mm thick 				
4.10.	RACK 22 HE <ul style="list-style-type: none"> ➤ Dimensions:120x600x600 ➤ Weight: up to 59 kg ➤ System door and side locks and two keys ➤ Thermally processed door glass, minimum 4mm thick 	1			
4.11	LED TV 32" <ul style="list-style-type: none"> ➤ Resolution (1366x768) ➤ 32" (80cm) ➤ LED LCD ➤ Digital audio out (optical) ➤ Scart (Full) ➤ 2 x HDMI ➤ CI Slot ➤ Wall mount included 	2			
4.12	UPS 1000VA <ul style="list-style-type: none"> ➤ 1000VA ➤ 600W ➤ Backup time: 10 minutes 	2			
4.13	HDD <ul style="list-style-type: none"> ➤ 2 TB capacity ➤ SATA 6Gb/s ➤ 7200 rpm ➤ Cache 64 MB ➤ 3,5 inch disk 	16			
4.14	Workstation Desktop Mini Tower <ul style="list-style-type: none"> ➤ "Mini Tower" chassis ➤ Blocking of all USB ports through the BIOS ➤ Processor: minimum two cores, Passmark CPU Mark 5600 or 	1			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<p>higher</p> <ul style="list-style-type: none"> ➤ Minimum 8 GB DDR3 SDRAM ➤ Upgradeable RAM to minimum 16 GB ➤ Minimum 2 TB HDD SATA II 7200rpm ➤ DVD-ROM drive, SATA ➤ Integrated network adapter 10/100/1000 ➤ Discrete graphic controller with 2GB dedicated DDR 3 RAM Memory; min. 700MHz GPU, outputs minimum: 2xDVI, 1xD-Sub, 1x HDMI ➤ Integrated HD audio controller + integrated speakers ➤ Ports in the front: Minimum 2 USB 3.0, audio in and out ➤ Ports in the rear: Minimum 6 USB ports (out of which minimum 2 USB 3.0 ports), audio in and out, Ethernet, VGA; ➤ Minimum 20" wide LCD Monitor from the same manufacturer as the Workstation Desktop, minimum resolution 1600x900, 5 ms response time or less, ➤ Keyboard – BiH layout, USB; ➤ Optical USB mouse, 2 buttons (with scroll button); ➤ MS Windows 8 Pro x64 – English <u>or equivalent</u>; ➤ Installation CD or DVD with all the drivers including Recovery disk; ➤ Energy star certified 				
	<p>Remark: For installation purposes, a contractor is obliged to provide power supply cables, connectors, plastic cable channels, AC adapters, fuse boxes and all other materials needed for system installation.</p>				

Contractor must deliver, install and put into operation video surveillance system in the building of judicial institutions in Tuzla (address: Maršala Tita 137, 75000 Tuzla). Contractor must provide one-day training how to operate the system to 5 staff members of the Court Police of Federation, Department Tuzla and supply system and user manual documentation in local language (Bosnian/Croatian/Serb).

Additional information regarding installation issues (installation paths, location of central system and monitoring components, positioning of each camera and its area coverage), with obligation of signing the confidentiality statement, will be provided during site survey of the building of judicial

institutions in Tuzla which will be organized according to Article 13 of Contract Notice and article 14 of Instructions to Tenderers.

Warranty period for all items: 1 year. Commercial warranty as granted by the manufacturer.

Lot 5 – IT equipment

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
5.1	Workstation Desktop <ul style="list-style-type: none"> ➤ “Small Form Factor” chassis ➤ Blocking of all USB ports through the BIOS ➤ Processor: minimum two cores, Passmark CPU Mark 4300 or higher ➤ Minimum 4 GB DDR3 SDRAM ➤ Upgradeable RAM to minimum 16 GB ➤ Minimum 500 GB HDD SATA II 7200rpm ➤ DVD/ROM drive, SATA ➤ Integrated network adapter 10/100/1000 ➤ Integrated HD graphic controller ➤ Integrated HD audio controller + integrated speakers ➤ Ports in the front: Minimum 2 USB 3.0, audio in and out ➤ Ports in the rear: Minimum 6 USB ports (out of which minimum 2 USB 3.0 ports), audio in and out, Ethernet, VGA; ➤ Minimum 20" wide LCD Monitor from the same manufacturer as the Workstation Desktop, minimum resolution 1600x900, 5 ms response time or less, ➤ Keyboard – BiH layout, USB; ➤ Optical USB mouse, 2 buttons (with scroll button); ➤ MS Windows 7 Professional – English <u>or equivalent</u>; ➤ Installation CD or DVD with all the drivers including Recovery disk; ➤ Energy star certified. 	11			
5.2	Copy Machine <ul style="list-style-type: none"> ➤ Standalone device ➤ Supported paper formats: A3, A4, A5 ➤ Drawer: A4, A3 ➤ Resolution: 1200 dpi x 1200 dpi; 	1			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	<ul style="list-style-type: none"> ➤ Print speed A4: minimum 45 pages/min bw ➤ First page out: less than 6 s ➤ Warm up time: maximum 12 sec from stand by; ➤ Duplex: Automatic duplex ➤ Paper capacity: minimum 500 sheets x 2 drawers (1000 sheets) ➤ Automatic duplex document feeder ➤ CPU: minimum 800 MHz ➤ RAM: minimum 1GB ➤ Built in Ethernet 10/100/1000 Mbps ➤ Integrated LCD touch screen; minimum 19 cm diagonal ➤ Power: 220/240 V ➤ Network protocol: TCP/IP (Support for IPv4/IPv6) ➤ Support for PCL6 ➤ Cassette: Two front cassette with 500 sheet capacity each (total 1000 sheets) ➤ Finisher: 1 tray, corner staple, tray minimum output capacity 1.000 sheets A4 				
5.3	<p>OCR – MRZ ID reader (Optical Character Recognition – Machine Readable Zone Identification Reader)</p> <ul style="list-style-type: none"> ➤ High resolution – cca 400 PPI with IR and UV illumination ➤ Hardware removing of reflections and OVD Overview ➤ Identification and verification of documents, as well as other personal documents, in accordance with ICAO standards ➤ Complete document processing (ICAO MRZ, General VIZ, RFID) ➤ ICAO MRZ reading - Documents under ICAO standard by ICAO specification 9303 part 1, part 1v2, part 2, part 3 and part 3v2 for the types of ID-1, ID-2 and ID-3 	3			

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
	MRZ OCR <ul style="list-style-type: none"> ➤ Reading of bar codes - 1D: UPC-A, EAN8, EAN13, Code39, Code128, ITF - 2D PDF 417, Data Matrix, QR Code, Aztec Code ➤ Contactless (RFID) reading - reading contactless integrated circuit in accordance with the standard ISO 14443 type A and B ➤ Provision of the software development kit (SDK) - Complete SDK including DLLs and demo programmes ➤ Programming languages - C/C++, C#, Visual Basic 6.0, Delphi, VB.NET, Java ➤ RFID functions ICAO Doc. 9303 LDS 1.7, ISO 18013 (driver's licences) PKI 1.1, BAC, EAC, EAC2.0, PACE, AA, PA, TA, CA, BAP, EAP ➤ Checking of data integrity MRZ vs. VIZ vs. bar codes vs. RFID IR B900 and UV paper inspection, inspection of passport holders' photos vs. RFID DG2 ➤ USB 2.0 connection 				

Items 5.1 and 5.2 must be delivered at the delivery location specified below.

For item 5.3: Contractor must deliver, install and put into operation the item at the location specified below.

Warranty period for all items: 1 year. Commercial warranty as granted by the manufacturer.

Delivery locations:

Institution	City	Address	5.1	5.2	5.3

Judicial Commission of the Brčko District of BiH	Brčko	Trg pravde 10, 76100 Brčko	11	1	
Court of Bosnia and Herzegovina	Sarajevo	Kraljice Jelene 88, 71000 Sarajevo			3
TOTAL			11	1	3

Lot 6 – Radio Communication Equipment

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
6.1	Digital handset <ul style="list-style-type: none"> ➤ UHF 403-470 MHz / VHF 136-174MHz ➤ Ion battery min 1800mAh ➤ digital/analog ➤ Frequency stability maximum +1.5ppm ➤ Earpiece, two wired with spiral and acoustic speaker ➤ Antenna ➤ Charger ➤ Belt clip ➤ Instruction manual 	50			
6.2	Digital Base Station with Software <ul style="list-style-type: none"> ➤ UHF 403-470 MHz / VHF 136-174MHz ➤ Output power: from 5 W to 50 W ➤ Number of channels: 16 ➤ digital/analog ➤ Frequency stability maximum +1.5ppm 	1			

For items 6.1 and 6.2: Contractor must deliver the items and incorporate them into existing digital radio system of the Court Police of Bosnia and Herzegovina, Kraljice Jelene 88, 71000 Sarajevo.

Additional information regarding installation will be provided during site survey of the building of judicial institutions of BiH, which will be organized according to Article 13 of Contract Notice and article 14 of Instructions to Tenderers, with obligation of signing the confidentiality statement.

Warranty period for all items: 1 year. Commercial warranty as granted by the manufacturer.

Lot 7 – Access Control Equipment

1	2	3	4	5	6
Item number	Specifications Required	Qty	Specifications Offered	Notes, remarks, ref to documentation	Evaluation Committee's notes
7.1	Plate number recognition camera <ul style="list-style-type: none"> ➤ IP digital camera ➤ Compatible with FORTRESS software for plate number recognition ➤ Resolution: 752 x 582 pixel ➤ OCR included ➤ Movement detection included ➤ Range: minimum of 15 m ➤ IR illumination with IR LED assembly ➤ Minimum speed of vehicles identified of 100 km / h ➤ Rotation up to 30 ° after installation ➤ Automatic mode ➤ Weather- proof housing 	2			
7.2	Metal detector <ul style="list-style-type: none"> ➤ It must have min 10 levels of sensitivity; ➤ It must possess adjustable audio warning; ➤ External dimensions of doors: 550-850 wide, 2200-2300 high, 240-650 (mm) long; ➤ Working conditions: -15 ° C - +50 ° C; ➤ Multizone - at least three real detection zones (left / middle / right); ➤ Auto-calibration. 	5			

For item 7.1: Contractor must deliver, install and incorporate the item into existing access control system for the judicial institutions of Bosnia and Herzegovina, Kraljice Jelene 88, 71000 Sarajevo.

Additional information regarding installation will be provided during site survey of the building of judicial institutions of BiH, which will be organized according to Article 13 of Contract Notice and article 14 of Instructions to Tenderers, with obligation of signing the confidentiality statement.

For item 7.2: Contractor must deliver and install/mount the item at the delivery locations mentioned below.

Warranty period for both all items: 1 year. Commercial warranty as granted by the manufacturer.

Delivery locations Item 7.2:

Institution	City	Address	7.2	Remark
Cantonal Prosecutor's Office of Una-Sana Canton	Bihać	Bosanska 2, 77000 Bihać	1	Equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH but the delivery and installation will be done by the contractor at the specified location.
Cantonal Prosecutor's Office of Middle-Bosnian Canton	Travnik	Aleja Konzula bb, 72270 Travnik	1	Equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH but the delivery and installation will be done by the contractor at the specified location.
Cantonal Prosecutor's Office of West-Herzegovina Canton	Široki Brijeg	Zaobilaznica bb, 88220 Široki Brijeg	1	Equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH but the delivery and installation will be done by the contractor at the specified location.
Municipal Court in Tuzla - Executive Department	Tuzla	Maršala Tita 137, 75000 Tuzla	1	Equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH but the delivery and installation will be done by the contractor at the specified location.
Municipal Court i Gradačac - Department Srebrenik	Srebrenik	221. oslobodilačke brigade 75350 Srebrenik	1	Equipment is to be recorded as an asset of the Head Office of the Court Police of FBiH but the delivery and installation will be done by the contractor at the specified location.